


Properties

	Description Enhanced grain, semi-aniline leather Available in 50 in-stock colors	Thickness 1.1mm +/- 0.1mm	Grain Characteristics Uniform
	Hide Size 55.00 sq. ft. avg.	Weight 2.75oz +/- 0.25oz per sq. ft.	Finish Characteristics Durable

Test Performance

AATCC Method 16, Option E Light Fastness Class 4-5 (72 hours)	ASTM D-2211 Elongation 30%-50% at 50 lbs.	ASTM D-4705 Stitch Tear 40 lbs.
ASTM D-2097 Newark Flex 70,000 cycles	ASTM D-3884 Abrasion Resistance 1,000+ cycles (CS-10)	ASTM D-5053 Crock Fastness Class 4-5 (dry rub) Class 4 (wet rub)
ASTM D-2208 Breaking Force 250 lbs.	AATCC 100-2004 Antibacterial Finishes Assessment & AATCC 147-2004 Antibacterial Activity Assessment Meets requirements for both	ASTM D1913-00 Resistance to Wetting Meets requirements

Flame Resistance

California TB 117	ASTM E84 Surface Burning Characteristics Class I*	FAR 25.853 (a) Am. 25-116, App. F, Part I (a)(1)(i)*
Boston Fire Code BFD-IX-1*	FMVSS 302	FAR 25.853 (a) Am. 25-116, App. F, Part I (a)(1)(ii)*
NFPA-260 Cigarette Ignition Class I	IMO A.652 (16) 8.2	FAR 25.853 (c) Am. 25-116, App. F, Part II (a)(4) and (5)*

Notes

- *Berkshire may be flame treated to meet required flammability regulations.
- Berkshire may be used in California TB 133 applications with suitable fire backers.
- Berkshire may be considered for all upholstery applications.

Showrooms

Atlanta
 Boston
 Charlotte
 Chicago
 Dallas
 Denver
 Honolulu
 Laguna Niguel
 Los Angeles
 New York
 Raleigh
 San Diego
 San Francisco

Scottsdale
 Troy
 Washington, DC

International

Australia
 Belgium
 Canada
 Chile
 Dubai UAE
 England
 France
 Greece
 Hong Kong
 New Zealand
 Portugal
 Spain
 Switzerland



1360 Niagara Street
 Buffalo, New York 14213
 800.342.7738 / 716.882.9301
 Fax 716.882.9358

www.garrettleather.com