

Properties

Description

Full grain, semi-aniline leather
Available in 50 in-stock colors

Hide Size

55.00 sq. ft. avg.

Thickness

1.1mm +/- 0.1mm

Weight

2.75oz +/- 0.25oz per sq. ft.

Grain Characteristics

Natural variations

Finish Characteristics

Light

Test Performance

AATCC Method 16, Option E Light Fastness

Class 4-5 (72 hours)

ASTM D-2097 Newark Flex

70,000 cycles

ASTM D-2208 Breaking Force

150 lbs.

ASTM D-2211 Elongation

30%-50% at 50 lbs.

ASTM D-3884 Abrasion Resistance

1,250+ cycles (CS-10)

ASTM D-4705 Stitch Tear

25 lbs.

ASTM D-5053 Crock Fastness

Class 4-5 (dry rub)
Class 4 (wet rub)

Flame Resistance

California TB 117

Boston Fire Code BFD-IX-1*

NFPA-260 Cigarette Ignition

Class I

ASTM E84 Surface Burning Characteristics

Class I*

FMVSS 302

IMO A.652 (16) 8.2

FAR 25.853 (a) Am. 25-116, App. F, Part I (a)(1)(i)*

FAR 25.853 (a) Am. 25-116, App. F, Part I (a)(1)(ii)*

FAR 25.853 (c) Am. 25-116, App. F, Part II (a)(4) and (5)*

Notes

*Caressa may be flame treated to meet required flammability regulations.

Caressa may be used in California TB 133 applications with suitable fire backers.

Caressa may be considered for all upholstery applications.

Showrooms

Atlanta
Boston
Charlotte
Chicago
Dallas
Denver
Honolulu
Laguna Niguel
Los Angeles
New York
Raleigh
San Diego
San Francisco

Scottsdale
Troy
Washington, DC

International

Australia
Belgium
Canada
Chile
Dubai UAE
England
France
Greece
Hong Kong
New Zealand
Portugal
Spain
Switzerland



1360 Niagara Street
Buffalo, New York 14213
800.342.7738 / 716.882.9301
Fax 716.882.9358

www.garrettleather.com