

Distressed

GREENGUARD
Indoor Air Quality Certified®

antiBACTERIAL

Properties



Description

Full grain, aniline leather
Available in 18 in-stock colors

Hide Size

55.00 sq. ft. avg.

Thickness

1.1mm +/- 0.1mm

Weight

2.75oz +/- 0.25oz per sq. ft.

Grain Characteristics

Natural variations

Finish Characteristics

Light wax

Test Performance

AATCC Method 16, Option E
Light Fastness

Class 2-3 (72 hours)

ASTM D-2208 Breaking Force
200 lbs.

ASTM D-2211 Elongation
30%-60% at 50 lbs.

ASTM D-4705 Stitch Tear
25 lbs.

ASTM D-5053 Crock Fastness
Class 2-3 (dry rub)

Flame Resistance

California TB 117

Boston Fire Code BFD-IX-1*

NFPA-260 Cigarette Ignition
Class I

ASTM E84 Surface Burning
Characteristics
Class I*

FMVSS 302

IMO A.652 (16) 8.2

FAR 25.853 (a) Am. 25-116,
App. F, Part I (a)(1)(i)*

FAR 25.853 (a) Am. 25-116,
App. F, Part I (a)(1)(ii)*

FAR 25.853 (c) Am. 25-116,
App. F, Part II (a)(4) and (5)*

Notes

*Distressed may be flame treated to meet required flammability regulations.

Distressed may be used in California TB 133 applications with suitable fire backers.

Distressed is an excellent choice for low to moderate traffic areas.

Showrooms

Atlanta
Boston
Charlotte
Chicago
Dallas
Denver
Honolulu
Laguna Niguel
Los Angeles
New York
Raleigh
San Diego
San Francisco

Scottsdale
Troy
Washington, DC

International

Australia
Belgium
Canada
Chile
Dubai UAE
England
France
Greece
Hong Kong
New Zealand
Portugal
Spain
Switzerland

Garrett
Leather

1360 Niagara Street
Buffalo, New York 14213
800.342.7738 / 716.882.9301
Fax 716.882.9358

www.garrettleather.com