

Mystique

GREENGUARD
Indoor Air Quality Certified®

Properties



Description

Enhanced grain, aniline leather
Available in 23 in-stock colors

Hide Size

50.00 sq. ft. avg.

Thickness

1.3mm +/- 0.1mm

Weight

3.25oz +/- 0.25oz per sq. ft.

Grain Characteristics

Pronounced

Finish Characteristics

Hand-tipped

Test Performance

AATCC Method 16, Option E Light Fastness

Class 4-5 (72 hours)

ASTM D-2097 Newark Flex

70,000 cycles

ASTM D-2208 Breaking Force

250 lbs.

ASTM D-2211 Elongation

30%-50% at 50 lbs.

ASTM D-4705 Stitch Tear

40 lbs.

ASTM D-5053 Crock Fastness

Class 4-5 (dry rub)

Class 4 (wet rub)

Flame Resistance

California TB 117

Boston Fire Code BFD-IX-1*

NFPA-260 Cigarette Ignition

Class I

ASTM E84 Surface Burning Characteristics

Class I*

FMVSS 302

IMO A.652 (16) 8.2

FAR 25.853 (a) Am. 25-116, App. F, Part I (a)(1)(i)*

FAR 25.853 (a) Am. 25-116, App. F, Part I (a)(1)(ii)*

FAR 25.853 (c) Am. 25-116, App. F, Part II (a)(4) and (5)*

Notes

*Mystique may be flame treated to meet required flammability regulations.

Mystique may be used in California TB 133 applications with suitable fire backers.

Mystique may be considered for all upholstery applications.

Showrooms

Atlanta
Boston
Charlotte
Chicago
Dallas
Denver
Honolulu
Laguna Niguel
Los Angeles
New York
Raleigh
San Diego
San Francisco

Scottsdale
Troy
Washington, DC

International

Australia
Belgium
Canada
Chile
Dubai UAE
England
France
Greece
Hong Kong
New Zealand
Portugal
Spain
Switzerland



1360 Niagara Street
Buffalo, New York 14213
800.342.7738 / 716.882.9301
Fax 716.882.9358

www.garrettleather.com