

# Pearlescence

GREENGUARD  
Indoor Air Quality Certified®

## Properties



### Description

Enhanced grain, semi-aniline leather  
Available in 21 in-stock colors

### Hide Size

55.00 sq. ft. avg.

### Thickness

1.1mm +/- 0.1mm

### Weight

2.75oz +/- 0.25oz per sq. ft.

### Grain Characteristics

Smooth

### Finish Characteristics

Pearl

## Test Performance

### AATCC Method 16, Option E

#### Light Fastness

Class 4-5 (72 hours)

### ASTM D-2097 Newark Flex

70,000 cycles

### ASTM D-2208 Breaking Force

150 lbs.

### ASTM D-2211 Elongation

30%-60% at 50 lbs.

### ASTM D-3384 Abrasion Resistance

1,000+ cycles (CS-10)

### ASTM D-4705 Stitch Tear

25 lbs.

### ASTM D-5053 Crock Fastness

Class 4-5 (dry rub)

Class 4 (wet rub)

## Flame Resistance

### California TB 117

### Boston Fire Code BFD-IX-1\*

### NFPA-260 Cigarette Ignition

Class I

### ASTM E84 Surface Burning Characteristics

Class I\*

### FMVSS 302

### IMO A.652 (16) 8.2

### FAR 25.853 (a) Am. 25-116, App. F, Part I (a)(1)(i)\*

### FAR 25.853 (a) Am. 25-116, App. F, Part I (a)(1)(ii)\*

### FAR 25.853 (c) Am. 25-116, App. F, Part II (a)(4) and (5)\*

## Notes

\*Pearlescence may be flame treated to meet required flammability regulations.

Pearlescence may be used in California TB 133 applications with suitable fire backers.

Pearlescence may be considered for all upholstery applications.

### Showrooms

Atlanta  
Boston  
Charlotte  
Chicago  
Dallas  
Denver  
Honolulu  
Laguna Niguel  
Los Angeles  
New York  
Raleigh  
San Diego  
San Francisco

Scottsdale  
Troy  
Washington, DC

### International

Australia  
Belgium  
Canada  
Chile  
Dubai UAE  
England  
France  
Greece  
Hong Kong  
New Zealand  
Portugal  
Spain  
Switzerland



1360 Niagara Street  
Buffalo, New York 14213  
800.342.7738 / 716.882.9301  
Fax 716.882.9358

[www.garrettleather.com](http://www.garrettleather.com)