

Properties



Description

Full grain, pure aniline leather
Available in 21 in-stock colors

Hide Size

58.00 sq. ft. avg.

Thickness

1.2mm +/- 0.1mm

Weight

3.00oz +/- 0.25oz per sq. ft.

Grain Characteristics

Natural variations

Finish Characteristics

Light wax

Test Performance

AATCC Method 16, Option E Light Fastness

Class 4 (72 hours)

ASTM D-2097 Newark Flex

70,000 cycles

ASTM D-2208 Breaking Force

250 lbs.

ASTM D-2211 Elongation

30%-60% at 50 lbs.

ASTM D-4705 Stitch Tear

50 lbs.

ASTM D-5053 Crock Fastness

Class 4 (dry rub)
Class 3 (wet rub)

Flame Resistance

California TB 117

Boston Fire Code BFD-IX-1*

NFPA-260 Cigarette Ignition
Class I

ASTM E84 Surface Burning
Characteristics
Class I*

FMVSS 302

IMO A.652 (16) 8.2

FAR 25.853 (a) Am. 25-116, App. F,
Part I (a)(1)(i)*

FAR 25.853 (a) Am. 25-116, App. F,
Part I (a)(1)(ii)*

FAR 25.853 (c) Am. 25-116, App. F,
Part II (a)(4) and (5)*

Notes

*Sierra may be flame treated to meet required flammability regulations.

Sierra may be used in California TB 133 applications with suitable fire backers.

Sierra is an excellent choice for low to moderate traffic areas.

Showrooms

Atlanta
Boston
Charlotte
Chicago
Dallas
Denver
Honolulu
Laguna Niguel
Los Angeles
New York
Raleigh
San Diego
San Francisco

Scottsdale
Troy
Washington, DC

International

Australia
Belgium
Canada
Chile
Dubai UAE
England
France
Greece
Hong Kong
New Zealand
Portugal
Spain
Switzerland



1360 Niagara Street
Buffalo, New York 14213
800.342.7738 / 716.882.9301
Fax 716.882.9358

www.garrettleather.com