

Properties

	Description Full grain, embossed nubuck Available in 21 in-stock colors	Thickness 1.4mm +/- 0.1mm	Grain Characteristics Pronounced
	Hide Size 52.00 sq. ft. avg.	Weight 3.50oz +/- 0.25oz per sq. ft.	Finish Characteristics Naked

Test Performance

AATCC Method 16, Option E Light Fastness Class 2-3 (72 hours)	ASTM D-2211 Elongation 30%-50% at 50 lbs.	ASTM D-5053 Crock Fastness Class 2-3 (dry rub)
ASTM D-2208 Breaking Force 150 lbs.	ASTM D-4705 Stitch Tear 25 lbs.	

Flame Resistance

California TB 117 Boston Fire Code BFD-IX-1* NFPA-260 Cigarette Ignition Class I	ASTM E84 Surface Burning Characteristics Class I* FMVSS 302	FAR 25.853 (a) Am. 25-116, App. F, Part I (a)(1)(i)* FAR 25.853 (a) Am. 25-116, App. F, Part I (a)(1)(ii)* FAR 25.853 (c) Am. 25-116, App. F, Part II (a)(4) and (5)*
---	---	--

Notes

- *Kenya may be flame treated to meet required flammability regulations.
- Kenya may be used in California TB 133 applications with suitable fire backers.
- Kenya is an excellent choice for low to moderate traffic areas.

Showrooms

Atlanta	New York
Charlotte	Philadelphia
Chicago	Raleigh
Cincinnati	San Diego
Dallas	San Francisco
Honolulu	Scottsdale
Houston	Seattle
Laguna Niguel	Troy
Los Angeles	Washington DC

International

Auckland
Dubai
Greece
Hong Kong
London
Paris
Switzerland
Sydney



1360 Niagara Street
Buffalo, New York 14213
800.342.7738 / 716.882.9301
Fax 716.882.9358

www.garrettleather.com