

## Properties



### Description

Full grain, aniline leather  
Available in 10 in-stock colors

### Hide Size

55.00 sq. ft. avg.

### Thickness

1.5mm +/- 0.1mm

### Weight

3.75oz +/- 0.25oz per sq. ft.

### Grain Characteristics

Pronounced

### Finish Characteristics

Hand-padded

## Test Performance

### AATCC Method 16, Option E Light Fastness

Class 4-5 (72 hours)

### ASTM D-2097 Newark Flex

70,000 cycles

### ASTM D-2208 Breaking Force

300 lbs.

### ASTM D-2211 Elongation

30%-60% at 50 lbs.

### ASTM D-3884 Abrasion Resistance

500+ cycles (CS-10)

### ASTM D-4705 Stitch Tear

50 lbs.

### ASTM D-5053 Crock Fastness

Class 4 (dry rub)

Class 3 (wet rub)

## Flame Resistance

### California TB 117

### Boston Fire Code BFD-IX-1\*

### NFPA-260 Cigarette Ignition

Class I

### ASTM E84 Surface Burning Characteristics

Class I\*

### FMVSS 302

### FAR 25.853 (a) Am. 25-116, App. F, Part I (a)(1)(i)\*

### FAR 25.853 (a) Am. 25-116, App. F, Part I (a)(1)(ii)\*

### FAR 25.853 (c) Am. 25-116, App. F, Part II (a)(4) and (5)\*

## Notes

\*Newport Club may be flame treated to meet required flammability regulations.

Newport Club may be used in California TB 133 applications with suitable fire backers.

Newport Club may be considered for all upholstery applications.

### Showrooms

Atlanta  
Charlotte  
Chicago  
Cincinnati  
Dallas  
Honolulu  
Houston  
Laguna Niguel  
Los Angeles

New York  
Philadelphia  
Raleigh  
San Diego  
San Francisco  
Scottsdale  
Seattle  
Troy  
Washington DC

### International

Auckland  
Dubai  
Greece  
Hong Kong  
London  
Paris  
Switzerland  
Sydney



1360 Niagara Street  
Buffalo, New York 14213  
800.342.7738 / 716.882.9301  
Fax 716.882.9358

[www.garrettleather.com](http://www.garrettleather.com)