


Properties

	Description Enhanced pebble grain, semi-aniline Available in 17 in-stock colors	Thickness 1.3mm +/- 0.1mm	Grain Characteristics Uniform
	Hide Size 48.00 sq. ft. avg.	Weight 2.75oz +/- 3.0oz per sq. ft.	Finish Characteristics Durable

Test Performance

AATCC Method 16, Option E Light Fastness Class 4-5 (72 hours)	ASTM D-2208 Breaking Force 250 lbs.	ASTM D-4705 Stitch Tear 40 lbs.
ASTM D-2097 Newark Flex 70,000 cycles	ASTM D-2211 Elongation 30%-50% at 50 lbs.	ASTM D-5053 Crock Fastness Class 4-5 (dry rub) Class 4 (wet rub)
ASTM D-3884 Abrasion Resistance 1,000+ cycles (CS-10)	AATCC 100-2004 Antibacterial Finishes Assessment & AATCC 147-2004 Antibacterial Activity Assessment Meets requirements for both	AATCC D-6014 Dynamic Water Absorption Excellent water resistance with less than 2% water absorption

Flame Resistance

California TB 117	ASTM E84 Surface Burning Characteristics Class I*	FAR 25.853 (a) Am. 25-116, App. F, Part I (a)(1)(i)*
Boston Fire Code BFD-IX-1*	FMVSS 302	FAR 25.853 (a) Am. 25-116, App. F, Part I (a)(1)(ii)*
NFPA-260 Cigarette Ignition Class I	IMO A.652 (16) 8.2	FAR 25.853 (c) Am. 25-116, App. F, Part II (a)(4) and (5)*

Notes

- *Torino may be flame treated to meet required flammability regulations.
- Torino may be used in California TB 133 applications with suitable fire backers.
- Torino may be considered for all upholstery applications.

Showrooms

Atlanta
 Boston
 Charlotte
 Chicago
 Dallas
 Denver
 Honolulu
 Laguna Niguel
 Los Angeles
 New York
 Raleigh
 San Diego
 San Francisco

Scottsdale
 Troy
 Washington, DC

International

Australia
 Belgium
 Canada
 Chile
 Dubai UAE
 England
 France
 Greece
 Hong Kong
 New Zealand
 Portugal
 Spain
 Switzerland



1360 Niagara Street
 Buffalo, New York 14213
 800.342.7738 / 716.882.9301
 Fax 716.882.9358

www.garrettleather.com