


Vintage

GREENGUARD
Indoor Air Quality Certified®

Properties

	Description Full grain, aniline leather Available in 7 in-stock colors	Thickness 1.1mm +/- 0.1mm	Grain Characteristics Natural variations
	Hide Size 55.00 sq. ft. avg.	Weight 2.75oz +/- 0.25oz per sq. ft.	Finish Characteristics Moderate gloss

Test Performance

AATCC Method 16, Option E Light Fastness Class 2-3 (72 hours)	ASTM D-2211 Elongation 30%-60% at 50 lbs.	ASTM D-5053 Crock Fastness Class 2-3 (dry rub)
ASTM D-2208 Breaking Force 200 lbs.	ASTM D-4705 Stitch Tear 25 lbs.	

Flame Resistance

California TB 117	ASTM E84 Surface Burning Characteristics Class I*	FAR 25.853 (a) Am. 25-116, App. F, Part I (a)(1)(i)*
Boston Fire Code BFD-IX-1*	FMVSS 302	FAR 25.853 (a) Am. 25-116, App. F, Part I (a)(1)(ii)*
NFPA-260 Cigarette Ignition Class I	IMO A.652 (16) 8.2	FAR 25.853 (c) Am. 25-116, App. F, Part II (a)(4) and (5)*

Notes

- *Vintage may be flame treated to meet required flammability regulations.
- Vintage may be used in California TB 133 applications with suitable fire backers.
- Vintage is an excellent choice for low to moderate traffic areas.

Showrooms

Atlanta
Boston
Charlotte
Chicago
Dallas
Denver
Honolulu
Laguna Niguel
Los Angeles
New York
Raleigh
San Diego
San Francisco

Scottsdale
Troy
Washington, DC

International

Australia
Belgium
Canada
Chile
Dubai UAE
England
France
Greece
Hong Kong
New Zealand
Portugal
Spain
Switzerland



1360 Niagara Street
Buffalo, New York 14213
800.342.7738 / 716.882.9301
Fax 716.882.9358

www.garrettleather.com