

RESILIENCE

PROPERTIES

DESCRIPTION

Italian natural grain, pure aniline leather.

AVERAGE HIDE SIZE

60.00 sq ft

THICKNESS

1.1 mm +/-0.1 mm

ATTRIBUTES

Paraffin wax and scratch resistant finish.
Unique variations and natural markings.

WEIGHT

2.75 oz +/-0.25 oz per sq ft

GRAIN CHARACTERISTICS

Natural variations

FINISH CHARACTERISTICS

Paraffin wax and scratch resistant finish

NON-TOXIC COMPOSITION

Our leathers are not made with nor contain conflict minerals, POPs, PVC, BPA, PDEs, plasticizers, heavy metals, or phthalates.

TEST PERFORMANCE

ABRASION

ASTM D-4157

Wyzenbeek Abrasion Resistance:
Class 5 at 100,000 cycles

ANTIBACTERIAL

AATCC 100

Assessment of Antibacterial Finishes
on Textile Materials (Quantitative):
Meets Requirements

AATCC 147

Assessment of Antibacterial Activity
of Textile Materials (Qualitative):
Meets Requirements

ENVIRONMENTAL

GREENGUARD Gold

Indoor Air Quality:
Certified

LIGHTFASTNESS

AATCC 16.3 Opt 3

Colorfastness to Light:
Class 3.5 at 72 hours

FLAMMABILITY

California Technical Bulletin

117 2013 Section E Flammability Test:
Certified

FAR 25.853 (a) Am. 25-116, App. F,
Part I (a)(1)(ii) Federal Aviation
Regulation for Flammability Resistance:
Passes with flame treatment

MVSS 302

Federal Motor Vehicle Safety Standards
Flammability of Interior Materials:
Certified

IMO Part 8: Upholstered Furniture
International Marine Organization
3.1 Cigarette Ignition:
Passed

IMO Part 8: Upholstered Furniture
International Marine Organization
3.2 Propane Flame:
Passed

NFPA 260

National Fire Protection Association
Cigarette Ignition Resistance:
Certified

BS 5852:2006:Source 5

British Standard Flammability Test:
Certified

*Resilience may be used in California
TB 133 applications with suitable fire
backers.*

DURABILITY Recommended for all upholstery applications.



PRODUCT CERTIFIED
FOR LOW CHEMICAL
EMISSIONS:
UL.COM/IGG
UL 2818



Antibacterial



FiberDye

GARRETT

LEATHER

800.342.7738
garrettleather.com