

SHAGARRETT

PROPERTIES

DESCRIPTION

Italian embossed semi-aniline leather.

AVERAGE HIDE SIZE

45.00 sq ft

THICKNESS

1.1 mm +/-0.1 mm

ATTRIBUTES

Stingray embossed leather with reverse tipping and no plate lines. Flame resistant. UV protected. Water and stain repellent dyed into the leather.

WEIGHT

2.75 oz +/-0.25 oz per sq ft

GRAIN CHARACTERISTICS

Embossed stingray

FINISH CHARACTERISTICS

Reverse tipped

APPROXIMATE PATTERN REPEAT

Vertical: 12.5"
Horizontal: 14.5"

PATTERN DIRECTION

Vertical

NON-TOXIC COMPOSITION

Our leathers are not made with nor contain conflict minerals, POPs, PVC, BPA, PBDEs, plasticizers, heavy metals, or phthalates.

Declare.



TEST PERFORMANCE

ABRASION

CS-10 Taber Abrasion Resistance:
1400 cycles

ABSORPTION

AATCC 79-2010
Absorbency of Textiles:
Meets Requirements

ANTIBACTERIAL

AATCC 100
Assessment of Antibacterial Finishes
on Textile Materials (Quantitative):
Meets Requirements

AATCC 147

Assessment of Antibacterial Activity
of Textile Materials (Qualitative):
Meets Requirements

ENVIRONMENTAL

GREENGUARD Gold
Indoor Air Quality:
Certified

FLAMMABILITY

California AB-2998;
Consumer products -
Flame Retardant Materials:
Passed

California Technical Bulletin
117 2013 Section E Flammability Test:
Certified

FAR 25.853 (a) Am. 25-116, App. F,
Part I (a)(1)(ii) Federal Aviation
Regulation for Flammability Resistance:
Passes with flame treatment

NFPA 260

National Fire Protection Association
Cigarette Ignition Resistance:
Certified

BS 5852:2006:Source 5

British Standard Flammability Test:
Certified

*Shagarrett may be used in California
TB 133 applications with suitable fire
backers.*

DURABILITY Excellent. Recommended for all upholstery applications, especially high traffic areas.



PRODUCT CERTIFIED
FOR LOW CHEMICAL
EMISSIONS:
UL.COM/IGG
UL 2818



LeatherShield™



Antibacterial



FiberDye®

GARRETT

LEATHER

800.342.7738
garrettleather.com