

# Wall Tiles | Wall Panels | Woven Panels

## STYLES

- Wall Tiles:** Wall tiles are custom made with any Garrett leather color adhered to the surface of recycled leather backing. Decorative stitching options are available.
- Wall Panels:** Wall panels may be specified as either flat or padded. Each panel is custom handcrafted with any Garrett leather color wrapped around ½ inch thick routed NAUF (No Added Urea Formaldehyde) MDF (medium density fiberboard) substrate. Decorative stitching options are available.
- Woven Panels:** Woven panels may be specified as either flat or padded. Each panel is custom handcrafted with Garrett Wovens® wrapped around ½ inch thick routed NAUF MDF substrate.

## SIZES

- 4x4, 8x8, 12x12, 18x18, 4x8, 2x10 parallelogram.  
Custom sizes are available.

## SPECIFICATIONS

- All tiles and panels are produced on a made to order basis. Please allow 10 -12 weeks for delivery.
- All MDF substrate is cut on a computer numeric control (CNC) machine.
- No added urea formaldehyde (NAUF) MDF is used exclusively to protect the health of those handling and living with Garrett Leather Wall Panels.

Style:	Wall Tile	Flat Panel	Padded Panel	Woven Panel
Content:	Specified leather adhered to recycled leather backer.	Specified leather fully wrapped and secured around routed MDF substrate.	Specified leather fully wrapped and secured around foam topped, routed MDF substrate.	Garrett Wovens® fully wrapped and secured around routed MDF substrate.
Thickness:	Approximately ⅛ inch depending on leather selected	Approximately ⅝ inch depending on leather selected	Approximately ¾ inch depending on leather selected	Approximately ⅝ inch depending on pattern selected
Installation Method:	Contact cement	Z clip system, 3M™ Dual Lock™, or drywall adhesive	Z clip system, 3M™ Dual Lock™, or drywall adhesive	Z clip system, 3M™ Dual Lock™, or drywall adhesive

## TEST PERFORMANCE

- ASTM E84 Class A materials can be used in construction. Please contact your sales representative for details.
- Padded Panels have a Noise Reduction Coefficient of .35
- Padded Panels have a Sound Absorption Average of .37
- Most Garrett products are GREENGUARD certified.

