

## PROPERTIES

### Description

Full grain, embossed nubuck, pure aniline leather. Available in 22 in-stock Fiberdye® colors.

### Attributes

Flame resistant. Water and stain repellent dyed into the leather.

### Average Hide Size

60.00 sq. ft.

### Thickness

1.4mm +/- 0.1mm

### Weight

3.50oz +/- 0.25oz per sq. ft.

### Grain Characteristics

Pronounced

### Finish Characteristics

Naked

## TEST PERFORMANCE

### ABRASION

#### CS-10

#### Taber Abrasion Resistance

3000 cycles

### ENVIRONMENTAL

#### GREENGUARD

#### Indoor Air Quality

Certified

### FLAMMABILITY

California Technical Bulletin  
117 Section E Flammability Test  
Certified

FAR 25.853 (a) Am. 25-116,  
App. F, Part I (a)(1)(ii)  
Federal Aviation Regulation  
for Flammability Resistance  
Passes with flame treatment

### FMVSS 302

Federal Motor Vehicle Safety Standards  
Flammability of Interior Materials

Certified

### IMO A.652(16)8.2

International Marine Organization  
Smouldering Cigarette Test

Passed

### IMO.A652(16)8.3

International Marine Organization 20  
Second Butane Flame Test

Passed

### NFPA 260

National Fire Protection Association  
Cigarette Ignition Resistance

Certified

### BS 5852:2006:Source 5

British Standard Flammability Test

Certified

### ASTM E84

Surface Burning Characteristics  
of Building Materials  
Class B

Kenya maybe used in California TB 133  
applications with suitable fire backers.

## DURABILITY

Recommended for moderate to low traffic areas.

Cracking, or color transfer, may occur with excessive rubbing or exposure to moisture.



Available Worldwide  
Visit [garrettleather.com](http://garrettleather.com) for a showroom in your area.



800.342.7738  
[www.garrettleather.com](http://www.garrettleather.com)